# CRL Tremco® Spectrem® 2 High Performance Silicone Sealant

SPEC. DATA MSDS

- High Performance in Demanding Applications
- Tools Easily, Cures Quickly




10.1 Fl. Oz. (300 ml);
30 Cartridges Per Case;
1800 Cartridges Per Pallet

Black | White | Gray | Anodized Aluminum

Colors shown are approximate

## Description

Tremco® Spectrem® 2 Silicone Sealant is a medium modulus, one-part, high performance, neutral cure sealant ideal for a variety of caulking and glazing applications.

## Basic Uses

CRL Tremco® Spectrem® 2 is suitable for both caulking and glazing applications, including cap beads, toe beads, heel beads, and other typical air seals. It is particularly appropriate as a weather seal and tensile bead in two-sided structural glazing systems, and ideal for sealing joints within the curtain/window wall systems.

## Comparable Sealants

**CRL:** 95C. **Dow Corning®**: 795, 995, 791. **GE®:** SilPruf® 2000, UltraGlaze® SSG 4000. **Tremco:** Spectrem® 3. **Pecora:** 864, 895. **Sonneborn:** OmniSeal. **Sika:** SikaSil®-WS95.

## Limitations

All structural glazing applications must be reviewed and approved by Tremco Technical Service prior to the application of Spectrem® 2. Do not apply to damp or contaminated surfaces. Check cartridge label and Specification Data Sheet for additional limitations.

## Technical Data

It meets or exceeds the test requirements of TT-S-001543A (COM-NBS) Class A; TT-S-00230C (COM-NBS) Class A, Type II; ASTM C-920 Type S, Grade NS, Class 50, Use NT, M, G, A, O.; CAN/CGSB-19.13-M87; AAMA 802.3-92 (Type I and II), 805.2-94 (Grade C), and 808.3-92.

**10.1 FL. OZ. (300 ML) CARTRIDGES**

| CAT. NO. | COLOR |
|---|---|
| 947802 | Black |
| 947806 | White |
| 947852 | Gray |
| 947878 | Anodized Aluminum |

Minimum order: 1 each. All cartridge sealants can be combined for quantity pricing.

# CRL Tremco® Tremsil 600 Silicone Sealant

SPEC. DATA MSDS

- Excellent Primerless Adhesion to Metal, Glass, Plastic, Rigid PVC, and Painted Surfaces
- Easy Gunning and Tooling Over a Wide Temperature Range
- Fast Cure




10.1 Fl. Oz. (300 ml);
30 Cartridges Per Case;
1800 Cartridges Per Pallet

Clear | White

Colors shown are approximate

## Description

CRL Tremco® Tremsil 600 Silicone Sealant is a one-part, medium modulus, neutral cure sealant. The sealant cures to a flexible rubber when exposed to moisture present in the air.

## Basic Uses

Tremsil 600 is compatible to most common, non-porous building component surfaces making it an excellent sealant for glazing of low rise residential windows. Tremsil 600 has excellent adhesion to aluminum, stainless steel, metals, glass, plastics, rigid P.V.C.'s, wood, brick, concrete, and painted surfaces.

## Comparable Sealants

**CRL:** RTV408 Silicone. **Dap:** Titanium®. **Dow Corning®:** 799 Silicone Contractors Weatherproofing, Vinyl Window, Siding and Door. **GE®:** 2800 SilGlaze II Silicone Contractors-N1800. **Pecora®:** 896 Silicone. **OSI:** VP-275. **Novagard®:** Novaflex Silicone. **Sika:** SikaSil®-N Plus.

## Limitations

Do not apply to damp or contaminated surfaces. Use with adequate ventilation. Check cartridge label and Specification Data Sheet for additional limitations.

## Technical Data

It conforms to ASTM C920 Type S, Grade NS, Class 25, Use NT, G, A and O; CAN/CGSB-19.13-M87; U.S. Federal Specification TT-S-00001543A (COM-NBS) Class A; U.S. Federal Specification TT-S-00230C (COM-NBS) Class A; AAMA 800-92 (802.3 - 92, 808.3-92).

**10.1 FL. OZ. (300 ML) CARTRIDGES**

| CAT. NO. | COLOR |
|---|---|
| 944800 | Clear |
| 944806 | White |

Minimum order: 1 each. All cartridge sealants can be combined for quantity pricing.